## (19) World Intellectual Property Organization International Bureau



(43) International Publication Date 1 April 2004 (01.04.2004)

**PCT** 

## (10) International Publication Number WO 2004/028170 A2

(51) International Patent Classification7:

H040

(21) International Application Number:

PCT/IB2003/004331

(22) International Filing Date:

3 September 2003 (03.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0222045.7

23 September 2002 (23.09.2002) G

(71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 ESPOO (FI).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SPIRITO, Maurizio [IT/FI]; Apollonkatu 4 A 19, FIN-00100 Helsinki (FI).
- (74) Agents: SLINGSBY, Philip, Roy et al.; Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

004/028170 A2

(54) Title: TERMINAL LOCATION

(57) Abstract: A method for locating a mobile terminal in a communications network, the method comprising the steps of: applying one of a plurality of available methods to estimate a location of the mobile terminal; and applying one of a plurality of available methods to calculate a region around the estimated location in which the mobile terminal could be located.